

Fiber Optic Splice Closure (Model: GJS03A-72 C)

General description: Fiber Optic Splice Closure GJS03A-72 C can be used in manhole, in handhole, aerial-hanger, wall-mounting, be directly buried and pedestal.



Dimension

Height:53cm,

Base diameter:16cm

closure ring dia. :21cm

4 small holes +1 oval hole

The diameter of the small holes is 2.0cm.The major axis of the oval hole(inside wall) is 6.cm,and the shorter axis of the oval hole is 4.cm.

Max. Fiber Capacity: $24 \times 6=144$ fibers

IP degree: IP 68

Working temperature: 40 degree ~ 110 degree

warranty: 25 years

Materials: closure body: PP splice tray: ABS

Content of fiber optic splice closure

- 1.Outer fixing part
- 2.Clamp
- 3.Dome



- 4.Base
- 5.Splice tray
- 6.Tray lid
- 7.Shield continuity wires
- 8.Valve
- 9Shield continuity connector
- 10.Sealing ring
- 11.Inner fixing part
- 12.Strength member
- 13.Support ring on the base
- 14.Velcro strip with one X flake

Oval outlet cable seal kit:

- 1.Heat shrinkable sleeve
- 2.Aluminum cable protection tapes
- 3.Abrasive strip
- 4.Branch off clip

Cable seal kit:

- 1.Aluminum cable protection tape
- 2.Heat shrinkable sleeve
- 3.Abrasive strip

Other accessories:

- 1.Desiccant
- 2.Shield continuity wires
- 3.Connector
- 4.Smouvs (splicing protection tubing)
- 5.transparent tubes
- Tie wraps

Installation flow chart

