

CONECTOR TIPO FAST CONNECT PARA NAP PRECONECTORIZADA

COMPATIBLE
CON TODAS LAS CAJAS



Fastconnect Translator

FAC Connector + Kit Body
(Base with Slim)

Optitap- Translator



APPLICATION

This field assenbly hardened connector is used for the optical link connection of the external access equipment of the passive optical network. One connector compatible with three interfaces. Most cost-effective and efficient solution.

FEATURES

- FAC Connector + Translator Structure, base with slim connector, compatible with Optitap and Fastconnect
- Assembly on site, simple operation
- Dont need special tool
- Suitable for indoor and outdoor use
- Water-proof, dust-free, anti-corrosion, weather ressistant
- Applicable for 5*2mm, 3*2mm Fig. 8, drop cable
- Compliance with IEC61754-4 SC-APC

Cable	5*2mm, 3*2mm Fig.8 Drop Cable
Fiber	G-657A2/ Bend Insensitive 9/125um -Coating: φ0.25mm
Insertion Loss (dB)	Avg. ≤0.3dB; Max. ≤0.5dB
Return Loss(dB)	UPC ≥45dB, APC ≥50dB
Mechanical Endurance	50 Times ΔIL ≤0.3dB
Tensile Strength	≥100N
Working Temperature	-25℃+70℃
Protection Level	IP68