

LF CAJA EMP PREMIUM M2

48-96 F



SPECIFICATION

Fiber Optic Splice Closure can be used in manhole, in handhole, aerial-hanger, wall-mounting, be directly buried and pedestal.



DIMENSION

Height:53cm,
Base diameter:16cm
closet ring dia. :21cm
4 small holes +1 oval hole
The diameter of the small holes is 2.0cm.The major axis of the oval hole(inside wall) is 6.cm,and the shorter axis of the oval hole is 4.cm.
Max. Fiber Capacity: $24 \times 6 = 144$ fibers
IP degree: IP 68
Working temperature: 40 degree ~ 110 degree
warranty: 25 years
Materials: closure body: PP splice tray: ABS

CONTENT OF FIBER OPTIC SPLICE CLOSURE

- | | |
|---------------------------|----------------------------------|
| 1.Outer fixing part | 8.Valve |
| 2.Clamp | 9.Shield continuity connector |
| 3.Dome | 10.Sealing ring |
| 4.Base | 11.Inner fixing part |
| 5.Splice tray | 12.Strength member |
| 6.Tray lid | 13.Support ring on the base |
| 7.Shield continuity wires | 14.Velcro strip with one X flake |

LF CAJA EMP PREMIUM M2

48-96 F



OVAL OUTLET CABLE SEAL KIT

- 1.Heat shrinkable sleeve
- 2.Aluminum cable protection tapes
- 3.Abrasive strip
- 4.Branch off clip



CABLE SEAL KIT

- 1.Aluminum cable protection tape
- 2.Heat shrinkable sleeve
- 3.Abrasive strip

OTHER ACCESSORIES

- 1.Desiccant
- 2.Shield continuity wires
- 3.Connector
- 4.Smouvs (splicing protection tubing)
- 5.transparent tubes Tie wraps

