

PON POWER METER

T-OP3213

MIDE EN
SIMULTÁNEO



DESCRIPCIÓN

MEDIDOR DE POTENCIA ÓPTICA PON SERIE OT-3000 ES PERFECTO PARA LA APLICACIÓN FTTX Y MANTENIMIENTO. ESTE MEDIDOR DE POTENCIA PUEDE PROBAR Y ESTIMAR SIMULTÁNEAMENTE LAS SEÑALES DE LA VOZ, DATOS Y VÍDEO. ES UNA HERRAMIENTA ESENCIAL E IDEAL PARA EL CONSTRUCCIÓN Y MANTENIMIENTO DE PROYECTOS DE PON.



ESPECIFICACIÓN

Measurement Range (dBm)	-40dBm~+10dBm
Output power(max)	15dBm
Isolation@1490/1550(dB)	>40dB
Burst mode measurement error	<±0.5dB
1490 downstream measurement	
Pass Zone(nm)	1535nm~1570nm
MeasurementRange(dBm)	-40dBm~+10dBm
Output power(max)	25dBm
Isolation@1310/1550(dB)	>40dB
1550 downstream measurement	
Pass Zone(nm)	1535nm~1570nm
Measurement Range(dBm)	-40dBm~+10dBm
Output power(max)	25dBm

PON POWER METER

T-OP3213



Isolation@1310/1490nm)	>40dB
Measurement Accuracy	
Connatural uncertainty(dB)	±0.5dB
Linearity(dB)	±0.1dB
Passing through insertion Loss(dB)	<1.5dB
General Information	
Detector Type	InGaAs
Optical Connector	FC/SC/ST Interchangeable/2.5 universal adapter
Fiber Type	SM 9/125um
Measurement Unit	dB/dBm/xW
Resolution (dB)	0.01dB
Operation Voltage(V)	DC 3.3V~5.5V
Power Supply	3pc1.5V battery
Continuously Operation time (h)	PON: 90h ;OPM: 100h
Operation Temperature(°C)	-10°C~60°C
Storage temperature(°C)	-10°C~60°C
Weight(kg)	423g

